



HSC Instructional Procedure for Goal Set-Up and Take-Down

Procedure for goal set-up

Goals will be stored under the deck at the HSC Clubhouse by 7:15 AM on game day. Each goal should consist of the following parts:

- 2 spikes (silver, look like nails)
- 2 upright pole spikes (Y shaped)
- 2 upright braces (silver with hooks on the end)
- 2 upright poles (purple with single hole ~12 inches from end)
- 2 crossbar poles (purple with 90 degree elbow)
- 1 crossbar joiner (silver or gold tube)
- 1 net... NET SHOULD HAVE BEEN LEFT ON ONE OF THE CROSSBAR POLES... **DO NOT REMOVE NET FROM CROSSBAR POLE**

Instructions:

- 1) Lay out uprights flat on ground with small holes located closest to bottom of the pole.
- 2) Lay out crossbars approximately where they will be inserted into the upright poles. The small length of the elbow should slide over the upright pole.
- 3) After upright poles have been connected to crossbars (still on ground), insert the crossbar joiner into one of the crossbar poles. Slide the other crossbar pole end over the joiner.
- 4) Insert hook end of upright braces into the holes on the upright poles (assembly still on ground).
- 5) Insert upright pole spikes into bottom of upright pole.
- 6) With upright poles positioned properly on end line, lift entire goal assembly to an upright position.
- 7) Push upright pole spikes into the ground. Do not force them as they will spread and no longer support the upright poles properly.
- 8) Nail upright braces into the ground behind goals with spikes. Do not drive nails all the way in yet.
- 9) Spread netting across crossbar, over upright poles and then hook the back corners of the net over the spikes. Drive the spikes the rest of the way in.
- 10) Fasten the net to upright braces using S-hooks attached to nets.

Procedure for goal takedown

The goals come apart in several pieces and get put back into the purple bags. The following pieces should be accounted for:

- 2 spikes (silver, look like nails)
- 2 upright pole spikes (Y shaped)
- 2 upright braces (silver with hooks on the end)
- 2 upright poles (purple with single hole ~12 inches from end)
- 2 crossbar poles (purple with 90 degree elbow)
- 1 crossbar joiner (silver or gold tube)
- 1 net... NET MUST REMAIN ON ONE OF THE CROSSBAR POLES... **DO NOT REMOVE NET FROM CROSSBAR POLE**

Simply disassemble the parts carefully. SLIDE THE NET OVER SO THAT IT IS ENTIRELY CONTAINED ON ONE OF THE CROSSBAR PIECES. **DO NOT REMOVE NET FROM CROSSBAR.**

Place all components in the bag, collect all four bags and return to HSC Clubhouse under deck.